



# REAR DISCHARGE CT

TYPE:  
HEAT EXCHANGER

FORM:  
BLOWER COIL

CAPACITY RANGE:  
1.16 KW -13.8KW



## DESIGN

- Sheet metal panels are fully powder coated for improved corrosion resistance.
- Drain nipple material able to handle high/low temperatures.
- Removable side covers on the unit makes accessibility easier.
- 250 series - New Removable drip tray makes heater element accessibility easier.
- Aluminum Side plates to reduce tube contact damage.
- 300 series - Heating elements are removable from the fin side of the coil.

## INNOVATIVE

- Compact design to take up less space.
- Rear discharge for confined spaces.
- **300 series**
  - Louvered Fin technology to improve heat transfer efficiency.
  - Micro groove tubing for improved efficiency.
  - 1/2" staggered Fin configuration.
  - External rotor motor

- 250 series
  - 3/8" staggered Fin configuration.
  - Shaded -pole motor

## QUALITY

- Manufactured under strict ISO 9001:2015 quality management
- All units are pressure tested to 30bar dry air.
- All fans are factory tested before dispatching.

## VERSATILE

- 9 Models Available
- 1-5 Fan variation
- Available in 6 and 4 FPI.
- Medium and Low Temperature.

## OPTIONAL EXTRA'S

- Bluchem Treatment
- Stainless Steel casing/Aluminium Fins
- Stainless Steel casing/Copper Fins
- Fan Isolator switch

